

**DURAL EPOXY PRIMER (1:1) PART B**

Version 2.

Print Date 06/30/2010

REVISION DATE: 06/07/2010

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : DURAL EPOXY PRIMER (1:1) PART B
 Product code : B2358

COMPANY : Euclid Chemical Company
 19218 Redwood Road
 Cleveland, OH 44110

Telephone : 1-800-321-7628
 Emergency Phone: : U.S. only: 1-800-424-9300
 International Users Call Collect: 1-703-527-3887

Product use : Curative

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Amber. Liquid. May cause slight irritation to the respiratory system. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
 Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting. May cause chemical burns to stomach, mouth, nose, and throat.
 Skin : May cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

May cause sensitization by contact. Prolonged skin contact may cause irritation, burns or dermatitis. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. May aggravate persons sensitized to amines. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Repeated inhalation of nonyl phenol may cause lung damage. Repeated skin contact with nonyl phenol may cause skin irritation and dermatitis. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
4-Nonylphenol	84852-15-3	30.0 - 60.0
Polyamide	NJ TSRN# 51721300-5644P	15.0 - 40.0
Benzyl alcohol	100-51-6	15.0 - 40.0

**DURAL EPOXY PRIMER (1:1) PART B**

Version 2.

Print Date 06/30/2010

REVISION DATE: 06/07/2010

Mixed Cycloaliphatic amines	NJ TSRN# 51721300-5917P	10.0 - 30.0
Heavy aromatic naphtha	64742-94-5	7.0 - 13.0
Tertiary Amine	NJ TSRN# 51721300-5918P	3.0 - 7.0
Tetraethylene pentamine	112-57-2	1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	> 200 °F, > 93 °C
Method	:	Setaflash Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes. Nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

**DURAL EPOXY PRIMER (1:1) PART B**

Version 2.

Print Date 06/30/2010

REVISION DATE: 06/07/2010

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection : Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Inspect and replace equipment at regular intervals. Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

No known components with exposure limits.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : Amber
- Odor : Ammonia
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.2
- % Volatile Weight : 57.2 %

SECTION 10 - REACTIVITY / STABILITY

- Substances to avoid : Oxidizing agents. Epoxies. Isocyanates. Acids.
- Stability : Material is stable under normal storage, handling, and use.
- Hazardous polymerization : Will not occur under normal conditions.

**DURAL EPOXY PRIMER (1:1) PART B**

Version 2.

Print Date 06/30/2010

REVISION DATE: 06/07/2010

SECTION 11 - TOXICOLOGICAL INFORMATION

Benzyl alcohol, CAS-No.: 100-51-6
 Acute oral toxicity (LD-50 oral) 1,580 mg/kg (Mouse) 1,940 mg/kg (Rabbit) 3,100 mg/kg (Rat) 1,230 - 3,100 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) 200 - 300 mg/l for 8 h (Rat) 1,000 mg/l for 8 h (Rat)

Tetraethylene pentamine, CAS-No.: 112-57-2
 Acute oral toxicity (LD-50 oral) 2,100 mg/kg (Rat) 2,100 mg/kg (Rat) 3,990 mg/kg (Rat)
 Acute dermal toxicity (LD-50 dermal) 660 mg/kg (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**TDG / DOT Shipping Description:**

UN1760, CORROSIVE LIQUID, N.O.S. (Alkaline Amine), 8, PG III

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Based on an evaluation of the components used, this product does not contain hazardous ingredients identified as per 29 CFR 1910.1200

OSHA Hazardous Components :

OSHA Status: Considered : Corrosive
hazardous based on the
following criteria:

OSHA Flammability : Not Regulated

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
97 g/l



DURAL EPOXY PRIMER (1:1) PART B

Version 2.

Print Date 06/30/2010

REVISION DATE: 06/07/2010

U.S. State Regulations:

MASS RTK Components	:	Benzyl alcohol	100-51-6
		Tetraethylene pentamine	112-57-2
Penn RTK Components	:	4-Nonylphenol	84852-15-3
		Polyamide	NJ TSRN# 51721300-5644P
		Benzyl alcohol	100-51-6
		Mixed Cycloaliphatic amines	NJ TSRN# 51721300-5917P
		Heavy aromatic naphtha	64742-94-5
		Tertiary Amine	NJ TSRN# 51721300-5918P
		Tetraethylene pentamine	112-57-2
NJ RTK Components	:	4-Nonylphenol	84852-15-3
		Polyamide	NJ TSRN# 51721300-5644P
		Benzyl alcohol	100-51-6
		Mixed Cycloaliphatic amines	NJ TSRN# 51721300-5917P
		Heavy aromatic naphtha	64742-94-5

Components under California Proposition 65:
None known.

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- | | |
|--|--|
| ACGIH - American Conference of Governmental Hygienists | PEL - Permissible Exposure Limit |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act |
| DOT - Department of Transportation | RTK - Right To Know |
| DSL - Domestic Substance List | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency | STEL - Short Term Exposure Limit |
| HMIS - Hazardous Materials Information System | TLV - Threshold Limit Value |
| IARC - International Agency for Research on Cancer | TSCA - Toxic Substances Control Act |
| MSHA - Mine Safety Health Administration | TWA - Time Weighted Average |
| NDSL - Non-Domestic Substance List | V - Volume |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound |
| NTP - National Toxicology Program | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration | |