

**DURALTEX 1705 A CLEAR 1GL CAN**

Version 1.

Print Date 03/13/2009

REVISION DATE: 01/03/2008

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : DURALTEX 1705 A CLEAR 1GL CAN  
 Product code : TA4371201000

COMPANY : Euclid Chemical Company  
 19218 Redwood Road  
 Cleveland, OH 44110

Telephone : 1-800-321-7628  
 Emergency Phone: : U.S. only: 1-800-424-9300  
 International Users Call Collect: 1-703-527-3887

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Clear to Yellow. Liquid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.  
 Eyes : Slightly irritating.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause sensitization.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

May cause sensitization by contact. Prolonged or repeated exposure to epoxy resin can cause irritation to skin, eyes, skin sensitization, temporary eye injury. Certain epoxy resins are reported to be mutagenic in some laboratory tests. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Ingestion

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Bisphenol A Polyglycidyl Ether Resin	25068-38-6	> 60.0
o-Cresyl glycidyl ether	2210-79-9	7.0 - 13.0
Formaldehyde Polymer with Toluene	25155-81-1	3.0 - 7.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get



**DURALTEX 1705 A CLEAR 1GL CAN**

Version 1.  
REVISION DATE: 01/03/2008

Print Date 03/13/2009

- |              |  |
|--------------|--|
|              | medical attention.   |
| Eye contact  | : Flush with water for 15 minutes. If irritation persists, get medical attention.                                    |
| Skin contact | : Wash with water. If irritation, rash or other disorders develop, get medical attention immediately.                |
| Ingestion    | : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately. |

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use.
- Hazardous combustion products : Smoke, fumes.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Personal protection equipment**
- Respiratory protection : Not required under normal conditions of use.
  - Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
  - Eye protection : Wear appropriate eye protection.
  - Skin and body protection : Not required.
  - Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.



**DURALTEX 1705 A CLEAR 1GL CAN**

Version 1.  
REVISION DATE: 01/03/2008

Print Date 03/13/2009

Engineering measures : General ventilation is sufficient.

**Exposure Limits**

No known components with exposure limits.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form : Liquid  
Color : Clear to Yellow  
Odor : Epoxy  
pH : Not available.  
Vapour pressure : Not available.  
Vapor density : Heavier than air  
Melting point/range : Not available.  
Freezing point : Not available.  
Boiling point/range : Not available.  
Water solubility : Miscible  
Specific Gravity : 1.147  
% Volatile Weight : 0.0 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Acids and bases.Amines.Epoxy curing agents.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Not regulated under RCRA. Dispose of in compliance with state and local regulations.  
Do not incinerate.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**



**DURALTEX 1705 A CLEAR 1GL CAN**

Version 1.  
REVISION DATE: 01/03/2008

Print Date 03/13/2009

NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Based on an evaluation of the components used, this product does not contain hazardous ingredients identified as per 29 CFR 1910.1200

OSHA Hazardous Components :

OSHA Flammability : Not Regulated

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 62 g/l

**U.S. State Regulations:**

Penn RTK Components : Bisphenol A Polyglycidyl Ether Resin 25068-38-6  
o-Cresyl glycidyl ether 2210-79-9  
Formaldehyde Polymer with Toluene 25155-81-1

NJ RTK Components : Bisphenol A Polyglycidyl Ether Resin 25068-38-6  
o-Cresyl glycidyl ether 2210-79-9  
Formaldehyde Polymer with Toluene 25155-81-1

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:  
108-88-3 Toluene

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



**DURALTEX 1705 A CLEAR 1GL CAN**

Version 1.

Print Date 03/13/2009

REVISION DATE: 01/03/2008

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System