

# QUIKRETE COMPANIES -- MORTAR MIX 1102 -- 5610-00N038881

=====  
Product Identification  
=====

Product ID:MORTAR MIX 1102  
MSDS Date:11/25/1986  
FSC:5610  
NIIN:00N038881  
MSDS Number: BRHPV  
=== Responsible Party ===  
Company Name:QUIKRETE COMPANIES  
Address:1790 CENTURY CIRCLE  
City:ATLANTA  
State:GA  
ZIP:30345  
Country:US  
Info Phone Num:404-634-9100  
Emergency Phone Num:404-634-9100  
Preparer's Name:OWEN E. BROWN  
CAGE:IO174

=== Contractor Identification ===

Company Name:QUIKRETE COMPANIES  
Address:1790 CENTURY CIRCLE  
Box:City:ATLANTA  
State:GA  
ZIP:30345  
Country:US  
Phone:404-634-9100  
CAGE:IO174

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PORTLAND CEMENT  
CAS:65997-15-1  
RTECS #:VV8770000  
Fraction by Wt: 13%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE:MAY CAUSE IRRITATION. SKIN:MAY DEVELOP SUFFICIENT HEAT TO CAUSE BURNS IF A LARGE MASS, SUCH AS A CAST OF A HAND OR ARM, IS KEPT IN CONTACT WITH SKIN WHILE HARDENING. INHAL:DUST IS CONSIDERED A NUI SANCE DUST. CHRONIC:NONE PRESENTLY KNOWN.  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:INGEST:HYDRAULIC CEMENT HARDENS WHEN WETTED. GET MD.  
EYE:FLOOD IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES. GET MD.  
SKIN:CAUSES CAUSTIC BURNING. WASH FROM SKIN. SEE MD. INGEST:CALL MD  
IMMEDAITELY ( ).

=====  
Fire Fighting Measures  
=====

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SWEEP OR VACUUM UP. AVOID CREATING EXCESSIVE DUST. SLURRY MAY PLUG DRAINS.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A DRY AREA.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPROVED NUISANCE DUST RESPIRATOR IF ABOVE TLV.  
Ventilation:GENERAL MECHANICAL EXHAUST.  
Protective Gloves:RUBBER GLOVES.  
Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:EMERGENCY EYE WASH AND DELUGE SHOWER .  
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.  
Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Spec Gravity:0.2  
Appearance and Odor:GRAY, ODORLESS POWDER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED BY MANUFACTURER.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL  
REGULATIONS FOR TRASH.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.