

**EUCO QWIKJOINT 200 PART B - 50 GALLON**

Version 2.

Print Date 05/19/2010

REVISION DATE: 05/06/2010

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : EUCO QWIKJOINT 200 PART B - 50 GALLON  
 Product code : 693B 55

COMPANY : Euclid Chemical Company  
 19218 Redwood Road  
 Cleveland, OH 44110

Telephone : 1-800-321-7628  
 Emergency Phone: : U.S. only: 1-800-424-9300  
 International Users Call Collect: 1-703-527-3887

Product use : Curative

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Clear. Liquid solution. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.  
 Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.  
 Ingestion : May cause irritation to the mouth, throat and stomach. May cause chemical burns to stomach, mouth, nose, and throat.  
 Skin : May cause moderate irritation. May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged and repeated overexposure to amines may cause liver and kidney damage based on animal studies. Animal studies have shown adverse effects in the pancreas, liver, thyroid and eyes caused by diethyltoluenediamine (DETDA). In rare instances, sensitization to DETDA has been reported to occur in humans. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Bis (2-propylheptyl) phthalate	53306-54-0	> 60.0
Diethyltoluenediamine	68479-98-1	15.0 - 40.0
Propoxylated Amine	102-60-3	3.0 - 7.0
6-Methyl-2,4-di(methylthio)-1,3-benzenediamine	102093-68-5	3.0 - 7.0
Amorphous silica	7631-86-9	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0

**EUCO QWIKJOINT 200 PART B - 50 GALLON**

Version 2.

Print Date 05/19/2010

REVISION DATE: 05/06/2010

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : > 200 °F, > 93 °C
- Method : Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide, carbon dioxide, and nitrogen oxides.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Store under normal warehouse conditions in sealed containers. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

**EUCO QWIKJOINT 200 PART B - 50 GALLON**

Version 2.

Print Date 05/19/2010

REVISION DATE: 05/06/2010

- Respiratory protection : Use full engineering controls before relying on personal protective equipment. Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Amorphous silica	7631-86-9	ACGIH TWA:	3 mg/m <sup>3</sup>	Respirable particles.
		ACGIH TWA:	10 mg/m <sup>3</sup>	Inhalable particles.
		OSHA PEL:	15 mg/m <sup>3</sup>	Total dust.
		OSHA PEL:	5 mg/m <sup>3</sup>	Respirable fraction.
		OSHA TWA:	0.8 mg/m <sup>3</sup>	
Titanium dioxide	13463-67-7	ACGIH TWA:	10 mg/m <sup>3</sup>	Total dust.
		OSHA PEL:	15 mg/m <sup>3</sup>	Total dust.
		OSHA TWA:	15 mg/m <sup>3</sup>	Total dust.
		OSHA TWA:	5 mg/m <sup>3</sup>	Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid solution
- Color : Clear
- Odor : Slight
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Not available.
- Specific Gravity : 1.1
- % Volatile Weight : 0.0 %

**SECTION 10 - REACTIVITY / STABILITY**

- Substances to avoid : Acids.
- Stability : Stable under normal conditions. Avoid welding arcs, flames or other high

**EUCO QWIKJOINT 200 PART B - 50 GALLON**

Version 2.

Print Date 05/19/2010

REVISION DATE: 05/06/2010

temperature sources.

Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Amorphous silica, CAS-No.: 7631-86-9

Acute oral toxicity (LD-50 oral) 22,500 mg/kg ( Rat ) 15,000 mg/kg ( Mouse )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

TDG / DOT Shipping Description:

NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

Amorphous silica 7631-86-9

Titanium dioxide 13463-67-7

OSHA Status: Considered : Irritant

hazardous based on the  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and  
exempt solvent) : 0 g/l

VOC Method 310 : 0 %



**EUCO QWIKJOINT 200 PART B - 50 GALLON**

Version 2.

Print Date 05/19/2010

REVISION DATE: 05/06/2010

**U.S. State Regulations:**

MASS RTK Components	:	Amorphous silica	7631-86-9
		Titanium dioxide	13463-67-7
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Penn RTK Components	:	Bis (2-propylheptyl) phthalate	53306-54-0
		Diethyltoluenediamine	68479-98-1
		Propoxylated Amine	102-60-3
		6-Methyl-2,4-di(methylthio)-1,3-benzenediamine	102093-68-5
		Amorphous silica	7631-86-9
		Titanium dioxide	13463-67-7
NJ RTK Components	:	Bis (2-propylheptyl) phthalate	53306-54-0
		Diethyltoluenediamine	68479-98-1
		Propoxylated Amine	102-60-3
		6-Methyl-2,4-di(methylthio)-1,3-benzenediamine	102093-68-5
		Amorphous silica	7631-86-9
		Titanium dioxide	13463-67-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	2
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- |  |   |
|--|---|
| ACGIH - American Conference of Governmental Hygienists                         | PEL - Permissible Exposure Limit                    |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act       |
| DOT - Department of Transportation   | RTK - Right To Know                                 |
| DSL - Domestic Substance List  | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency  | STEL - Short Term Exposure Limit                    |
| HMIS - Hazardous Materials Information System                                  | TLV - Threshold Limit Value                         |
| IARC - International Agency for Research on Cancer                             | TSCA - Toxic Substances Control Act                 |
| MSHA - Mine Safety Health Administration                                       | TWA - Time Weighted Average                         |
| NDSL - Non-Domestic Substance List   | V - Volume  |
| NIOSH - National Institute for Occupational Safety and Health                  | VOC - Volatile Organic Compound                     |
| NTP - National Toxicology Program  | WHMIS - Workplace Hazardous Materials Information   |



EUCLID CHEMICAL

**EUCO QWIKJOINT 200 PART B - 50 GALLON**

Version 2.

Print Date 05/19/2010

REVISION DATE: 05/06/2010

System

OSHA - Occupational Safety and Health Administration